

Declaration of Performance

according to Annex III of the Regulation (EU) No. 305/2011 (Construction Products Regulation)

Mulcol® Multiwrap

No. DoP-PSS-MW

1. Unique identification code of the product-type:

Mulcol® Multiwrap, Fire wrap

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See batch number on the packaging of the product.

- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
- 3.1 The intended use of the system Mulcol® Multiwrap is to restore fire resistance of flexible wall, solid wall and solid floor structures where they are interrupted by various installations, as listed in ETA 23/0054.
- 3.2 The conditions under which the system Multiwrap can be used for sealing penetrations are intended for indoor and outdoor application without exposure to rain (TR 024, Type Y_1).
- 3.3 The provisions made in this DoP are based on an assumed working life of the Mulcol® Multiwrap for 25 years, provided that the conditions laid down in the manufacturer's datasheet and instructions for the packaging, transport, storage, installation, use and repair are met. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Mulcol International PO Box 93 4330 AB Middelburg The Netherlands

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP-System 1

- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: Not applicable
- 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

This Declaration of Performance has been prepared in accordance with the guidelines set out within EAD 350454-00-1104. ETA 23/0054 was prepared by UL International B.V. notified body 2821, Certificate of Constancy of Performance 2821-CPR-0257.



9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	C-s1,d0	EN 13501-1
Resistance to Fire	ETA 23/0054	EN 13501-2
Air permeability	NPD	EN 1026
Water permeability	NPD	EAD 350454-00-1104 Annex C
Release of dangerous substances	IA1, S/W3	EOTA TR 034
Mechanical Resistance and stability	NPD	EOTA TR 001
Resistance to impact/movement	NPD	EOTA TR 001
Airborne sound insulation	NPD	EN 10140-2
Impact sound insulation	NPD	EN 10140-3
Thermal properties	NPD	EN 12664, EN 12667 or EN 12939
Water vapor permeability	NPD	EN ISO 12572, EN 12086
Durability and serviceability	Type: Y ₁	EOTA TR 024

NPD: No performance determined

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on the behalf of the manufacturer by:

Ing. W. Scheffer-Geuze Technical Director

